

# MOTORCYCLE GROUND ANCHOR WITH TWIN LAYER PROTECTION

MODEL NO: MCGA01D

Thank you for purchasing a Sealey product. Manufactured to a high standard, this product will, if used according to these instructions, and properly maintained, give you years of trouble free performance.

IMPORTANT: PLEASE READ THESE INSTRUCTIONS CAREFULLY. NOTE THE SAFE OPERATIONAL REQUIREMENTS, WARNINGS & CAUTIONS. USE THE PRODUCT CORRECTLY AND WITH CARE FOR THE PURPOSE FOR WHICH IT IS INTENDED. FAILURE TO DO SO MAY CAUSE DAMAGE AND/OR PERSONAL INJURY AND WILL INVALIDATE THE WARRANTY. KEEP THESE INSTRUCTIONS SAFE FOR FUTURE USE.



Refer to instruction manual

### 1. SAFETY

- WARNING! The warnings, cautions and instructions referred to in this manual cannot cover all possible conditions and situations that may occur. It must be understood that common sense and caution are factors which cannot be built into this product, but must be applied by the operator. It is the operator's responsibility to secure the load.
- ✓ Locate the anchor in a suitable area. Keep area clean and tidy and free from unrelated materials and ensure that there is adequate lighting.
- ✓ Ensure that the floor/wall is level and strong enough (preferably concrete) to resist attempts to pull the anchor from it's fixings.
- √ Keep children and unauthorised persons away from work area.
- √ Inspect unit before each use. Check fasteners for tightness, replace any worn or damaged parts.
- **DO NOT** attempt to use a unit that is damaged in any way.
- **DO NOT** modify the unit in any way.
- **DO NOT** use the unit for a purpose it is not designed to perform.
- DO NOT use the unit if it is damaged.

### 2. INTRODUCTION

Heavy-duty hardened steel ground anchor. The twin layer design gives you extra security and peace of mind. Perfect to be used with heavy-duty chains and locks to provide a secure locking point for items such as motorcycles, bicycles, boats, caravans and trailers. Bolts down to any solid surface and is suitable for indoor and outdoor use. Includes anti-tamper bearings and all fixings needed to set this up.

# 3. SPECIFICATION

## 4. INSTALLATION

- **4.1.** Select a mounting surface that is suitably strong and flat in order to support the anticipated loads.
- **4.2.** Drill four holes to suit the M10 x 70mm rawl bolts (supplied) on a 110mm x 110mm pitch square.
- **4.3.** Offer up the anchor plate to the holes and insert the rawl bolts when aligned.
- 4.4. When the rawl bolts and anchor plate are firmly in place, drive the ball bearing (supplied) into the hex socket in the head of the bolt.
  - □ WARNING!: Once the ball bearing is driven into the socket, it will not be possible to remove it, hence also the rawl bolt.

## 5. MAINTENANCE

- **5.1.** Keep the anchor clean and wipe off any oil or grease.
- **5.2.** Before each use check all parts. If any part of the anchor is damaged or defective, remove it from service and take the necessary action to remedy the problem.





## **ENVIRONMENT PROTECTION**

Recycle unwanted materials instead of disposing of them as waste. All tools, accessories and packaging should be sorted, taken to a recycling centre and disposed of in a manner which is compatible with the environment. When the product becomes completely unserviceable and requires disposal, drain any fluids (if applicable) into approved containers and dispose of the product and fluids according to local regulations.

**Note**: It is our policy to continually improve products and as such we reserve the right to alter data, specifications and component parts without prior notice.

**Important**: No Liability is accepted for incorrect use of this product.

Warranty: Guarantee is 12 months from purchase date, proof of which is required for any claim.



Jack Sealey Ltd t/a Sealey Group, Kempson Way, Suffolk Business Park, Bury St Edmunds, Suffolk, IP32 7AR UK Jack Sealey (EU) Ltd t/a Sealey Group, Farney Street, Carrickmacross, Co. Monaghan, A81 PK68 Ireland
Tel: 01284 757500 • Email: sales@sealey.co.uk • Web: www.sealey.co.uk

© Jack Sealey Limited Original Language Version MCGA01D Issue:2 13/08/25