Section 1. Product and Company Identification.

1.1 Model Number; SCS034 v1 / SCS034S v1

1.2 Description; Grey Zinc Primer Paint 500ml Pack of 6
Grey Zinc Primer Paint 500ml - Single

1.3 Manufacturer;

Jack Sealey Ltd.
t/a Sealey Group.
Kempson Way,
Bury St. Edmunds,
Suffolk,
IP32 7AR
UK

Jack Sealey (EU) Ltd
t/a Sealey Group.
Farney Street,
Carrickmacross,
Co. Monaghan,
A81 PK68
Ireland

technicalcompliance@sealey.co.uk

1.4 Emergency telephone number; 44 (0) 1284 757 500 (Office Hours)

Date of source compilation; 13/05/2025

Section 2. Hazards Identification.

2.1 Classification of the substance or mixture.

Aerosol, Category 1:	H222; H229
Skin corrosion/irritation, Category 2:	H315
Serious eye damage/eye irritation, Category 2:	H319
Specific target organ toxicity – Single exposure, Category 3, Narcosis:	H336
Specific target organ toxicity – Repeated exposure, Category 2:	H373
Hazardous to the aquatic environment – Chronic Hazard, Category 2:	H411

Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects.

Pressurised container: May burst if heated. Extremely flammable aerosol. May cause drowsiness or dizziness. Causes serious eye irritation.

2.2 Label elements.

Hazard pictogram(s)



Signal Word: Danger

Contains: Xylene (mixture of isomers); Acetone

Hazard statements;

H222 - Extremely flammable aerosol.
H229 - Pressurised container: May burst if heated.
H315 - Causes skin irritation.
H319 - Causes serious eye irritation.
H336 - May cause drowsiness or dizziness.
H373 - May cause damage to organs through prolonged or repeated exposure.
H411 - Toxic to aquatic life with long lasting effects.

Precautionary statements;

P102 - Keep out of reach of children.
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 - Do not spray on an open flame or other ignition source.
P251 - Do not pierce or burn, even after use.
P260 - Do not breathe vapours, spray.
P271 - Use only outdoors or in a well-ventilated area.
P280 - Wear protective gloves, eye protection.
P264 - Wash hands thoroughly after handling.
P332+P313 - If skin irritation occurs: Get medical advice/attention.
P312 - Call a POISON CENTER, doctor if you feel unwell.
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337+P313 - If eye irritation persists: Get medical advice/attention.
P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50.
P501 - Dispose of contents/ container in accordance with local regulations.

EUH-statements:

EUH066 - Repeated exposure may cause skin dryness or cracking.

Child-resistant fastening:

Not applicable

Tactile warning:

Applicable

2.3 Other hazards.

Contains no PBT and/or vPvB substances ≥ 0.1% assessed in accordance with REACH Annex XIII

Section 3. Substances.

3.1 Chemical Name (substance)	**3.1 CAS No.**	**3.2 Concentration Volume**	**Classification**	
			Hazard Class & Category Code	**Hazard Statements [1]**
Petroleum gases, liquefied (Contains < 0.1% 1,3-butadiene)	68476-85-7	25 – 50%	Flam. Gas 1A	H220
Acetone	67-64-1	25 – 50%	Flam. Liq. 2 Eye Irrit. 2 STOT SE 3	H225 H319 H336
Xylene (mixture of isomers)	1330-20-7	10 – 20%	Flam. Liq. 3 Acute Tox. 4 (Dermal) Acute Tox. 4 (Inhalation) Skin Irrit. 2 Eye Irrit. 2 STOT SE 3 STOT RE 2 Asp. Tox. 1	H226 H312 H332 H315 H319 H335 H373 H304
Zinc powder - zinc dust (stabilised)	7440-66-6	10 – 20%	Aquatic Acute 1 Aquatic Chronic 1	H400 H410
Ethylbenzene	100-41-4	1 – 2.5%	Acute Tox. 4 (Inhalation) Acute Tox. 4 (Inhalation:dust,mist) STOT RE 2 Asp. Tox. 1 Aquatic Chronic 3	H332 H332 H373 H304 H412
1-methoxypropan-2-ol	107-98-2	1 – 2.5%	Flam. Liq. 3 STOT SE 3	H226 H336
Quartz (SiO2)	14808-60-7	0.005 – 0.05%	-	-
Methyl methacrylate	80-62-6	0.005 – 0.05	Flam. Liq. 2 Skin Irrit. 2 Skin Sens. 1 STOT SE 3	H225 H315 H317 H335

Cont.

3.1 Chemical Name (substance)	3.1 CAS No.	3.2 Concentration Volume	Classification	
			Hazard Class & Category Code	Hazard Statements [1]
Butyl methacrylate	97-88-1	0.005 – 0.05%	Flam. Liq. 3 Skin Irrit. 2 Eye Irrit. 2 Skin Sens. 1 STOT SE 3	H226 H315 H319 H317 H335
2-methoxypropanol	1589-47-5	0.005 – 0.05	Flam. Liq. 3 Skin Irrit. 2 Eye Dam. 1 Repr. 1B STOT SE 3	H226 H315 H318 H360D H335

[1]For full text of Statements, see Section 16.

Section 4. First Aid Measures.

4.1 Description of first aid measures

First Aid measures, general.
Call a poison centre or a doctor if you feel unwell.

Inhalation
Remove person to fresh air and keep comfortable for breathing.

Skin Contact
Wash skin with plenty of water. Take off contaminated clothing. If skin irritation occurs: Get medical advice/attention.

Eye Contact
Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

Ingestion
Call a poison centre or a doctor if you feel unwell.

Self protection of the first-aider
First aid workers will be equipped with suitable personal protective equipment

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effect:	May cause drowsiness or dizziness.
Symptoms/effects after inhalation:	None under normal conditions.
Symptoms/effects after skin contact:	Irritation.
Symptoms/effects after eye contact:	Eye irritation.
Symptoms/effects after ingestion:	None under normal conditions.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

Section 5. Fire Fighting Measures.

5.1. Extinguishing media

Suitable extinguishing media:	Water spray. Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media:	Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Fire hazard:	Extremely flammable aerosol.
Explosion hazard:	Pressurised container: May burst if heated.
Hazardous decomposition products in case of fire:	Toxic fumes may be released.

5.3. Advice for fire-fighters

Firefighting instructions:	Fight fire from safe distance and protected location. Do not enter fire area without proper protective equipment, including respiratory protection.
Protection during firefighting:	Do not attempt to action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

Section 6. Accidental Release Measures.

6.1. Personal precautions, protective equipment and emergency procedures

General measures:	Stop leak if safe to do so. Notify authorities if product enters sewers or public waters. Absorb spillage to prevent material damage.
For non-emergency personnel:	
Protective equipment:	Wear recommended personal protective equipment.
Emergency procedures:	Ventilate spillage area. No open flames, no sparks, and no smoking. Do not breathe dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes.
For emergency responders:	
Protective equipment:	Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
Emergency procedures:	Evacuate unnecessary personnel. Stop leak if safe to do so.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up:

For containment:	Collect spillage. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Stop leak without risks if possible.
Methods for cleaning up:	Mechanically recover the product.
Other information:	Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

See Section 7 for information on Safe Handling

See Section 8 for information of Personal Protective Equipment.

See Section 13 for information on disposal.

Section 7. Handling and Storage.

7.1. Precautions for safe handling

Additional hazards when processed:	Not expected to present a significant hazard under anticipated conditions of normal use.
Precautions for safe handling:	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Use only outdoors or in a well-ventilated area. Avoid breathing dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes. Wear personal protective equipment.
Hygiene measures:	Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures:	Keep in a cool, well-ventilated place away from heat.
Storage conditions:	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store locked up. Store in a well-ventilated place. Keep container tightly closed.
Packaging materials:	Always store product in container of same material as original container.

7.3. Specific end use(s)

Intended for use as a Grey Zinc Primer Paint for the Model Number identified in 1.1 with Description stated in 1.2.

Section 8. Exposure Controls/Personal Protection.

8.1. Control parameters
Workplace exposure limits.

Substance	CAS number	Workplace exposure limit. Long term.		Short term.	
		ppm	$mg.m^3$	ppm	$mg.m^3$
Petroleum gases, liquefied (Contains < 0.1% 1,3-butadiene)	68476-85-7	1000	1750	1250	2180
Acetone	67-64-1	500	1210	1500	3620
Xylene (mixture of isomers)	1330-20-7	50	220	100	441
Ethylbenzene	100-41-4	100	441	125	552
1-methoxypropan-2-ol	107-98-2	100	375	150	560
Methyl methacrylate	80-62-6	50	208	100	416

8.2. Exposure controls
Appropriate Engineering Controls
Ensure good ventilation of the workstation.

Personal protective equipment:
Wear recommended personal protective equipment.

Eye/Face Protection:
Safety glasses

Skin Protection:
Wear suitable protective clothing

Hand Protection:
Protective gloves

Respiratory Protection:
In case of insufficient ventilation, wear suitable respiratory equipment

Environmental exposure controls:
Avoid release to the environment

Section 9. Physical and Chemical Properties.

9.1. Information on basic physical and chemical properties

The following information is not a technical specification or sales specification.

(a) Appearance:	Aerosol, silver/grey liquid.
(b) Odour:	Organic solvent.
(c) Odour threshold;	No data available.
(d) pH:	Substance/mixture is non-soluble (in water).
(e) Melting point/freezing point;	No data available.
(f) Initial boiling point and boiling range;	-40 to -2 °C (LPG)
(g) Flash point;	< -40 °C
(h) Evaporation rate;	No data available.
(i) Flammability (solid, gas);	Extremely flammable aerosol.
(j) Upper/lower flammability or explosive limits;	Upper: 10.9 vol % (LPG) Lower: 1.4 vol % (LPG)
(k) Vapour pressure;	590-1760 kPa (LPG)
(l) Density;	No data available.
(m) Relative density;	No data available.
(n) Solubility(ies);	No data available.
(o) Partition coefficient: n-octanol/water;	No data available.
(p) Auto-ignition temperature;	365 °C (LPG)
(q) Decomposition temperature;	No data available.
(r) Viscosity;	< 20.5 mm^2/s
(s) Explosive properties;	Pressurised container. May burst if heated
(t) Oxidising properties.	No data available.

9.2 Other information

% of flammable ingredients;	77.938%
VOC Content;	614 g/l.
Volatility;	Volatile

Section 10. Stability and Reactivity.

10.1. Reactivity	Extremely flammable aerosol. Pressurised container: May burst if heated.
10.2. Chemical stability	Stable under normal conditions.
10.3. Possibility of hazardous reactions	No dangerous reactions known under normal conditions of use.
10.4. Conditions to avoid	Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.
10.5. Incompatible materials	No data available.
10.6. Hazardous decomposition products	Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11. Toxicological Information.

11.1. Information on toxicological effects

Inhalation
No data available.

Ingestion
No data available.

Skin contact
Causes skin irritation.
pH: Not relevant - substance/mixture is non-soluble (in water).

Eye contact
Causes serious eye irritation.
pH: Not relevant - substance/mixture is non-soluble (in water).

Section 12. Ecological Information.

12.1. Toxicity	Toxic to aquatic life with long lasting effects.
12.2. Persistence and degradability	Not rapidly degradable.
12.3. Bioaccumulative potential	No data available.
12.4. Mobility in soil	No data available.
12.5. Results of PBT and vPvB assessment	No data available.
12.6. Other adverse effects	No data available.

Section 13. Disposal Considerations.

13.1. Waste treatment methods

Regional waste regulation:	Disposal must be done according to official regulations.
Waste treatment methods:	Dispose of contents/container in accordance with licensed collector's sorting instructions.
Sewage disposal recommendations:	Disposal must be done according to official regulations.
Product/Packaging disposal recommendations:	Disposal must be done according to official regulations.
Additional information:	Do not re-use empty containers.
Ecological waste information:	No data available.

Section 14. Transport Information.

ADR. International Carriage of Dangerous Goods by Road.

14.1. UN number	UN 1950		
14.2. Name and Description	AEROSOLS, flammable		
	Label		2.1
	Special Provisions		190 344 625
	Limited Quantities		1 L
	Excepted Quantities		E0
	Packing Instructions		P207, LP02
	Special Packaging Provisions		RR6 L2
14.3. Transport hazard class(es)	Class		2
	Classification Code		5F
	Transport Category		2
	Tunnel restriction code		D
14.4. Packing group	-		
14.5. Environmental hazards	Avoid release to the environment		
14.6. Special precautions for user	Refer to Section 2.2 Precautionary Statements		

IATA. International Air Transport Association.

14.1. UN number	UN 1950		
14.2. UN Proper Shipping Name/Description	AEROSOLS, flammable		
	Hazard Label.		Flamm. gas
	Excepted Quantity		E0
	Packaging Instructions	Passenger	203
		Ltd Qty	Y203
		Cargo	203
		ERG Code	10L
	Special Provisions		A167

Special Provision A802.
Notwithstanding the absence of a packing group in column E, substances and article assigned to these entries must be packed in UN Specification packagings that meet packing group II performance standards. This does not apply when aerosols are prepared for transport in accordance with the limited quantity provisions.

14.3. Transport hazard class(es)	Class or Division	2.1
14.4. Packing group	-	
14.5. Environmental hazards	Avoid release to the environment	
14.6. Special precautions for user	Refer to Section 2.2 Precautionary Statements	

IMDG. International Maritime Dangerous Goods.

14.1. UN number	UN 1950	
14.2. UN proper shipping name	AEROSOLS, flammable	
	Special Provisions	63, 190 277, 327, 344, 959
	Limited Quantities	See Special Provision 277
	Excepted Quantities	E0
	Packaging Instructions	P207, LP02
	Packaging Provisions	PP87, L2
14.3. Transport hazard class(es)	Class or Division	2
	Subsidiary Risk(s)	See Special Provision 63
14.4. Packing group	-	
14.5. Environmental hazards	Avoid release to the environment	
14.6. Special precautions for user	Refer to Section 2.2 Precautionary Statements	
14.7. Transport in bulk – Maritime only.	Bulk transport is not applicable to this product	

Section 15. Regulatory Information.

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture
No data available.

15.2. Chemical safety assessment
No data available.

Section 16. Additional Information.

Full text of Statements used in Section 3;
H220 Extremely flammable gas.
H225 Highly flammable liquid and vapour.
H226 Flammable liquid and vapour.
H304 May be fatal if swallowed and enters airways.
H312 Harmful in contact with skin.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H319 Causes serious eye irritation.
H332 Harmful if inhaled.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.
H360 May damage fertility or the unborn child.
H373 May cause damage to organs through prolonged or repeated exposure.
H400 Very toxic to aquatic life.
H410 Very toxic to aquatic life with long lasting effects.
H412 Harmful to aquatic life with long lasting effects.

The above information is believed to be accurate and represents the best information currently available.
No warranty is expressed or implied by the above information.
We assume no liability resulting from use of the above information.
The end user should conduct their own investigations to determine the suitability of the above information for their particular purpose.

Issue level	Date	Revisions
1	04/03/2016	First issue.
2	15/09/2016	Sections 3.2, 14 & 15.
3	14/10/2020	Section 2.2, 3 & 16.
4	16/11/2026	Section 3.

End of Safety Data Sheet.